

# ROLL OUT RACKS

MANUFACTURED BY  **INDUSTRIUM**

## REQUEST QUOTATION FOR ROLL OUT PALLET (RACK MOUNT)

Date: \_\_\_\_\_ / \_\_\_\_\_ / \_\_\_\_\_

Dealer: \_\_\_\_\_

Branch city/State: \_\_\_\_\_

Salesperson name: \_\_\_\_\_

Salesperson email: \_\_\_\_\_

Salesperson phone: \_\_\_\_\_

Customer name: \_\_\_\_\_

Customer city: \_\_\_\_\_

## SPECIFICATIONS

**QUANTITY:** \_\_\_\_\_

**Frame dimension:**  40" wide x 42" deep  40" wide x 48" deep  Other \_\_\_\_\_

**Top plate dimension:**  46" x 42"  42" x 42"  46" x 48"  42" x 48"  Other \_\_\_\_\_

Top plate perforated Yes (Standard)

No holes, smooth

Top plate 1" side and 1" back lips

No side and back lips

Custom side height \_\_\_\_\_

Custom back height \_\_\_\_\_

Lock in (standard)

Lock in - Lock-out

**Roll out extension: 75%**

**Capacity: 1000 lbs UDL**

## WILL BE INSTALLED ON

**Frame dimension:** \_\_\_\_\_ X \_\_\_\_\_ X \_\_\_\_\_ Length

**Frame dimension:**  Box  Step

- Recommandations:**
- 2 ROLL OUT PALLETS PER BAY, MINIMUM REQUIRED LEVEL CAPACITY: 5000 LBS
  - 3 ROLL OUT PALLETS PER BAY, MINIMUM REQUIRED LEVEL CAPACITY: 6000 LBS
  - OPENING ONE ROLL OUT PALLET AT A TIME
  - RACK BEAMS MUST BE BOLTED TO THE UPRIGHTS
  - UPRIGHTS PROPERLY ANCHORED TO THE FLOOR
  - FOLLOW RACK MANUFACTURER'S RECOMMANDATIONS AT ALL TIME