

## REQUEST QUOTATION FOR ROLL OUT PALLET (RACK MOUNT)

Date: \_\_\_\_\_ / \_\_\_\_\_ / \_\_\_\_\_ Dealer: \_\_\_\_\_

Branch city/State: \_\_\_\_\_ Salesperson name: \_\_\_\_\_

Salesperson email: \_\_\_\_\_ Salesperson phone: \_\_\_\_\_

Customer name: \_\_\_\_\_ Customer city: \_\_\_\_\_

## SPECIFICATIONS

**QUANTITY:** \_\_\_\_\_

**Frame dimension:** ☐ 30" W x 42" D ☐ 40" W x 48" D ☐ 40" W x 36" D ☐ Other \_\_\_\_\_

**Top plate dimension:** ☐ 34" ☐ 42" ☐ 46" ☐ 52" ☐ Other \_\_\_\_\_

**Lips:** ☐ 1" ☐ No"

☐ Top plate perforated Yes (Standard) ☐ No holes, smooth ☐ Custom

☐ Top plate 1" side and 1" back lips (boxes) ☐ No side and back lips (skids)

☐ Lock in (standard) ☐ Lock in - Lock-out (\$ Fee)

**Maximum extension: 75%**

**Capacity: 1000 lbs UDL / 2000 lbs UDL**

## WILL BE INSTALLED ON

**Frame dimension:** \_\_\_\_\_ X \_\_\_\_\_ X \_\_\_\_\_ Lenght

**Frame dimension:** ☐ Box ☐ Step

**Recommandations:**

- 2 ROLL OUT PALLETS PER BAY, MINIMUM REQUIRED LEVEL CAPACITY: 5000 LBS
- 3 ROLL OUT PALLETS PER BAY, MINIMUM REQUIRED LEVEL CAPACITY: 6000 LBS
- OPENING ONE ROLL OUT PALLET AT A TIME
- RACK BEAMS MUST BE BOLTED TO THE UPRIGHTS
- UPRIGHTS PROPERLY ANCHORED TO THE FLOOR
- FOLLOW RACK MANUFACTURER'S RECOMMANDATIONS AT ALL TIME

